



# NICHIAS FGS SDN BHD (Co. No. 203309 H)

Head Office/Factory  
Plot 103, Darulaman Industrial Estate  
Bandar Darulaman, 06000 Jitra,  
Kedah Darul Aman, Malaysia  
Tel: 04-917 3760 Fax: 04-917 5964

Kuala Lumpur Sales Office  
Lot 3, Lorong SS 13/3D, Subang Jaya Industrial Area,  
Off Jalan SS 13/3, 47500 Subang Jaya,  
Selangor Darul Ehsan, Malaysia  
Tel: 03-5636 4067 Fax: 04-5636 4078








## HIGH DENSITY YELLOW GAS LINE

The preferred PTFE thread seal tape for handling natural gas (NG), liquid petroleum gas (LPG) and other hydrocarbons.



### 5 REASONS ON WHY YOU SHOULD USE TOMBO HIGH DENSITY YELLOW GAS LINE TAPES:

-  **Stringently tested\***  
For handling Gasoline, Petroleum Oils, Propane, Butane, Naptha, Benzene, Kerosene, and Natural Gas.  
\* Certified by Underwriters Laboratories (UL®)
-  **Leak Tight**  
Ultra high density (1.40 g/cm<sup>3</sup>) ensures that PTFE tapes sit into threads without shredding or tearing.
-  **Cost Effective**  
Only a Minimum of Two Full spiral wound wraps required for a leak tight seal.
-  **Flame Resistant**  
PTFE cannot burn, char or melt.
-  **SAFETY CANNOT BE COMPROMISED!**

### PRODUCT SPECIFICATIONS

**Material** : Polytetrafluoroethylene (PTFE)  
**Tape Color** : Yellow  
**Thickness** : 0.09mm (In accordance to GSA: A-A-58092)  
**Density** : 1.40 g/cm<sup>3</sup> (In accordance to ASTM D6585 Type 1)  
**Temp. Range** : -40°C to +150°C  
**Certified Working Pressure:**  
 Rating up to 300PSIG

\*Rating up to 100PSIG also available for less critical applications.

### COMPLIANCES AND APPROVALS:

Underwriters Laboratories (UL®), File No: MH25476  
 Australian Gas Association (AGA), App. No. 6635  
 American Society for Testing & Materials (ASTM, D6585 Type 1)  
 General Service Administration (GSA), A-A-58092  
 Japanese Industrial Standards (JIS), K 6885

